



## Specifications

- > Rugged ABS housing - X722
  - > Stainless steel housing - X722s
  - > Transparent dust-cover included
  - > Big LCD display with backlit
  - > High accuracy up to 1/60,000
  - > Adjustable pole holder
  - > Zero and tare function
  - > Hi-Ok-Lo checkweigher
  - > Animal weighing
  - > Accumulating
  - > Counting function
  - > Recall function
  - > Low battery indication
  - > Auto power off
  - > Multi units exchange
  - > Multi-interval selectable
  - > 22 function keys
- Numeric 0~9, Sample, Count, Backlight, M+, Recall, MC, Hi. Lo, I/O set, Print, CE, PT, Units, Net/Gross, Zero, Tare, On, Off
- > Optional RS232 for printer or computer - X7001
  - > Optional bluetooth output - X7002
  - > Optional plastic wall supporter - X7003
  - > Optional s.s bracket - X7004

## Technical Data

<b>Power</b> 100-240V - 12V1Ah Adaptor Rechargeable Battery: 6V4Ah Estimated Battery Life: 300 hours - single 1*350Ω load cells, no backlit LCD (40mm) Charge Time: 8 hours	<b>Non-Linearity</b> ≤ 0.01%F.S.	<b>Protection</b> IP54 - X722 IP65 - X722s
<b>Excitation Voltage</b> DCSV 1-8 * 350Ω or 1-16*750Ω load cells	<b>Display</b> 40mm	<b>Approval</b> CE
<b>Sensitivity</b> 0.12uV/d minimum	<b>Units</b> Kg   lb   g   oz, etc.	<b>Packing Size</b> 76*46*34cm (8pcs)
<b>Analog Input</b> 0.6mV/V - 3mV/V	<b>Output</b> RS232 (optional) Bluetooth (optional)	<b>Packing Weight</b> 18Kg (X722) 26Kg (X722s)
<b>A/D Rate</b> 30 times/second	<b>Operating Temperature</b> -10°C - 45°C 14°F - 104°F	
<b>Internal Resolution</b> 300,000 - 600,000	<b>Storage Temperature</b> -25°C - 55°C	
	<b>Relative Humidity</b> ≤80% non-condensing	



## Models

Part No.	110049	110050	157013	157014	157015	157016
Models	X722	X722s	X7001	X7002	X7003	X7004
Display	LCD	LCD	-	-	-	-
Protection	IP54	IP65	-	-	-	-
Weight	2.3kg	3.2kg	-	-	-	-